


Accessories

Solis Data Logging Box

Ginlong Monitoring System



Data Logging Box
DLB

Data Logging Box: WiFi

- Quick installation and easy operation
- Monitor your system and data anytime via Wi-Fi
- Easy visualization of data and other information via Internet
- Comprehensive analysis in the event of a fault

Data Logging Box: GPRS

- Quick installation and easy operation
- GPRS communication supporting remote monitoring
- Multi-functional protections keeping your system from faults
- Keeping users informed of status and data via mobile device

Datasheet

Model	DLB-W(WiFi)	DLB-G(GPRS)
Max. number of inverters	10	
Inverter communication	RS485	
Remote communication	WiFi (802.11 b/g/n)	GPRS
Max. communication range	<1km	
Communication rate	9600bps (adjustable:1200-57600 bps)	
WiFi frequency	2.4GHz	850/900/1800/1900 MHz
WiFi communication range	300m in outdoor open area without obstruction	/
WiFi transmitting power	802.11b/g/n: +20dBm/+18dBm/15dBm (Max)	Class 4 (2W) / Class 1 (1W)
Data collect intervals	5 minutes (adjustable:1-20 minutes)	
Preferences setting	Web server/Serial AT instruction	Serial AT instruction
Firmware updates	Serial/Wireless	
Data access	Serial/WiFi point-to-point/Remote server	Serial/Remote server
Status display	4 LEDs	

Electrical

Input voltage	DC 5V	
Static power consumption	<1.6W	<2W
Max. instantaneous power consumption	<2.5W	<8W

Environmental

Operating temperature	-10~65°C	
Operating humidity	10%-90% Relative humidity, no condensa	
Storage temperature	-40~65°C	
Storage humidity	<40%	
Protection class	IP21	

Physical

Dimensions (L*W*H)	110mm*86mm*26mm	
Weight	108g	102g

Other

Certificates	FCC, CE, RoHS	
--------------	---------------	--